## जाहिर निविदा

शहर अभियंता, पनवेल महानगरपालिका हद्दीतील प्रभाग समिती -अ , ब . क , ड, मधील विविध भुखंडांवर दैनिक बाजार बांधणे या कामाचे अंदाजपत्रक बनविण्याकरीता खाली नमूद केलेल्या बाबींकरीता दर मागविण्यात येत आहे.

अ. क्र.	कामाचे नाव	मुदत		
१	पनवेल महानगरपालिका हद्दीतील प्रभाग समिती - अ , ब . क , ड, मधील विविध भुखंडांवर दैनिक बाजार बांधणे.	०९ /०५ /२०२५  ते १५/०५ /२०२५  (७ दिवस		

Index	Fixture Type	Tender Specification	Unit	Quantity
1	ACP CNC Cutting Works	For CNC cutting of aluminum composite panels (ACPs),technical specifications: standard panel sizes (e.g., 8x4 feet or 2440mm x 1220mm), thicknesses (4mm), aluminum skin thickness (0.12mm to 0.5mm), and core materials (LDPE or mineral)  CNC Cutting Considerations:  Saw Blades: Use carbide-tipped blades designed for aluminum.  Cutting Speeds: Recommended cutting speeds of 3000 to 5000 rpm.  Grooving: For U-grooving, leave 0.2 to 0.4mm of the core material.  Bending: Grooved panels can be folded using a folding jig, plate punch, or press brake.  Rout and Return System: A method for creating a tray-type panel by routing a V-shaped groove and folding the edges.  CNC Machines: Use CNC routers specifically designed for aluminum.  Finishing: Ensure clean cutting edges free of burrs by clamping the panel material to prevent vibration.  Tolerances and Accuracy: Specify the exact dimensions, shapes, cuts, perforations, and tolerances required for the panel machining.  Warranty complaince: Minimum 20-25 Years	Sq.M	1

2	RCC SAUCER DRAIN	Supply of RCC SAUCER DRAIN Size - 600 mm x 300mm x 100mm M30 GRADE	Nos	1
3	PREACOATED SOLID ALUMINIUM SHEETS PVDF WITH PERFORATION AS PER DRAWING	PRECOATED Solid Alumnium Sheets PVDF with Perforation as per drawing Alloy: 3000 Series Size: 2.4M x 1.2 M sheets thickness 2 mm Colour:RAL- as per the attached image Coating Thickness: 25/30 Mic + backside Primer Origin: M/s LUXECOAT –ITALY. (EUROPE).  Tolerances - 3% +/- Warranty complaince: Minimum 20-25 Years	Sq.M	1
4	VALLEY GUTTER WORKS	Providing and fixing of 2mm thick Aluminium Non-Insulated gutter (Girth 600mm) with Necessary down take spout diameter upto 150 mm at required intervals & other accessories like Cover plate, end caps and welding at joints to be provided. The Girth of gutter would be upto 600mm. Dye Penetration test to be conducted wherever aluminium welding has been done. (The material shall be Powder Coating of same roofing sheet colour).	Rmt	1

वर नमूद सुचित दर्शविलेल्या बार्बीचे पुरवठा करणारे पुरवठादार/दुकानदार/उत्पादक/विक्रेते यांनी नमूद केलेल्या बार्बीकरीता असलेले दर स्वत:च्या लेटरहेडवर महापालिकेच्या कार्यालयात अथवा ई-मेल द्वारे pmcbandhkamdept01@gmail.com यावर दिनांक ०३/०४/२०२५ पर्यंत पाठवावे ही विनंती, सदर दर हे अंदाजपत्रक तयार करणेसाठी गृहित धरणेत येणार आहे

कार्यकारी अभियंता पनवेल महानगरपलिका

जा.क्र पमपा/बांधकाम/ ५०२५ /प्र.क्र. ०४ /१६४७ /२०२५ दि . ०८/०५/२०२५

## प्रत माहितीस्तव -

- १. प्रसिध्दीकरीता
- २. माहिती फलक करीता